



Specifications

F.O.B Sedalia, Missouri 65301



303

OPTIONS:

- Safety pilots
- Stainless steel liner - **FMOD-SS-LINER**
- Stainless steel feet - **SS-FEET**
- Adapter plates - **31, 32, 33**
- Telescope covers - **546, 548**
- Spillage pans - **576, 676**
- Stainless steel cutting board in lieu of poly
- Hardwood cutting board in lieu of poly
- Drop type brackets for cutting board
- Standard serving shelf - **656-x**
- Deluxe serving shelf - **956-x**
- Standard buffet shelf - **63x**
- Deluxe buffet shelf - **83x**
- 3-bar tray slide - **3BTS-x**
- Stainless steel dish shelf under cutting board - **441S-x**
- Solid stainless tray slides - **SOLID-FX/HD**

AGENCY LISTINGS:



DUKE MANUFACTURING CO.
 2305 N. Broadway
 St. Louis, MO 63102

800.735.3853 Toll Free
 314.231.5074 Fax
 www.dukemfg.com

Approval Stamp(s):

PRODUCT INFORMATION:

PROJECT: _____
 ITEM: _____
 QUANTITY: _____

MODEL:

Aerohot™ Steamtables Hot Food Units - Gas

- 302** 2 top openings
- 303** 3 top openings
- 304** 4 top openings
- 305** 5 top openings

TOP:

- 20 gauge, 300 Series stainless steel
- Die-stamped openings - 12" x 20"
- Poly carving board - 7"W x 1/2" thick with 18 gauge stainless steel support base and die-stamped brackets

HEAT COMPARTMENTS:

- Die-formed galvanized steel - 8" deep
- Insulated on all four sides and bottom with fiberglass

BODY AND INTERIOR SHELF:

- 20 gauge, 430 Series stainless steel body
- 20 gauge, 430 Series stainless steel undershelf
- 430 Series stainless steel tubular legs with adjustable plastic feet

CONTROLS

- Natural or Propane, as specified
- Galvanized steel radiation plate in each compartment
- Gas pressure regulator furnished in each unit
- Burners controlled by individual adjustable valves

SHORT FORM SPECIFICATIONS:

Aerohot™ Steamtables - Hot Food - Gas. Top shall be heavy gauge, 300 Series stainless steel with body, undershelf and legs formed of heavy gauge 430 Series stainless steel. Top shall have die-stamped openings, measuring 12" x 20". Units to be furnished with poly carving board measuring 7" x 1/2" thick with 18 gauge stainless steel support base and die-stamped brackets. Die-formed heat compartments, 8" galvanized liner, each insulated on all four (4) sides and bottom with 1" thick fiberglass or equal, with thermal conductivity of 0.27 or less. Each compartment shall have individual burner rated at 2500 BTU for propane or 1,000 BTU for natural. Burners controlled by adjustable valve. Galvanized radiation plate in each compartment and gas pressure regulator to be furnished. Unit shipped semi-knocked down.

NOT AVAILABLE ON CASTERS • SPECIFY NATURAL OR PROPANE


Aerohot

MODEL:


**Aerohot™ Steamtables
Hot Food Units - Gas**

- 302 2 top openings
- 303 3 top openings
- 304 4 top openings
- 305 5 top openings


LEGEND	
	GAS CONNECTION



TOP VIEW



FRONT VIEW



RIGHT SIDE VIEW

DIMENSIONS:

Freight Class: 85

Model	Length		Width		Height		Top Openings	Cube ft. Crated	Weight	
	in.	cm	in.	cm	in.	cm			lbs.	kg
302	30-3/8	77.2	22-7/16	57.1	34	86.4	2	23.4	92	41.8
303	44-3/8	112.8	22-7/16	57.1	34	86.4	3	32.5	109	49.6
304	58-3/8	148.3	22-7/16	57.1	34	86.4	4	41.5	139	63.2
305	72-3/8	183.9	22-7/16	57.1	34	86.4	5	50.5	166	75.5

POWER SUPPLY: High altitude orifice available - specify elevation. **SPECIFY NATURAL OR PROPANE.**

Model	# Burners	Total BTU
302	2	5,000
303	3	7,500
304	4	10,000
305	5	12,500

NOTE: No combustible materials should be stored on bottom shelf. NOT AVAILABLE IN PORTABLE MODELS



DUKE MANUFACTURING CO.

2305 N. Broadway
St. Louis, MO 63102

800.735.3853 Toll Free
800.231.1130 In Missouri
314.231.5074 Fax
www.dukemfg.com

Specification subject to change

01/10
Printed in U.S.A
© 2010, Duke Manufacturing Co.