

HOBART701 S Ridge Avenue, Troy, OH 45374
1-888-4HOBART • www.hobartcorp.com**HBP77I HOLDING &
TRANSPORT CABINET****HOBART****STANDARD FEATURES**

- Two separately controlled heated holding and transport cabinets in one compartment with individual capacity of 7 each 18" x 26" sheet pans, 14 each 12" x 20" x 2½" pan, or a combination of both on 3" centers
- Heavy duty 5" casters (2 swivel with brake, 2 rigid)
- Recessed control panel containing dual indicator light (red when connected to power and amber when heating elements are in operation), thermometer, and full range thermostat for temperatures up to 190°F
- Fully insulated 1½" side walls and 2" in top
- Heavy duty polished stainless steel construction; 20 gauge exterior, 22 gauge interior
- Removable universal tray slides provide for easy cleaning
- 4 pairs of universal tray slides adjustable on 1½" centers per compartment
- 120 volt, 2400 watts, 30 amp
- Single 6' heavy duty cord and NEMA 5-30 plug
- Positive action door latch

OPTIONS

- Complete with full perimeter bumper
- 208/240 volt (no charge)
- Left hand hinge door (no charge)
- Stacking kit
- Card holder
- Cord wrap
- Additional universal tray slides
- Humidity pan

MODEL

- HBP77I — Holding and Transport Cabinet

Specifications, Details and Dimensions on Reverse Side.


**HBP77I HOLDING & TRANSPORT CABINET**

HBP77I HOLDING & TRANSPORT CABINET



701 S Ridge Avenue, Troy, OH 45374
1-888-4HOBART • www.hobartcorp.com

DETAILS AND DIMENSIONS



Model No.	Capacity 12" x 20" x 2½"	Capacity 18" x 26"	High	Deep	Wide	Shipping Weight	Volts	Watts	Amps
HBP77I	14	7	72½"	31¾"	24½"	400 lbs.	120	2400	30

As continued product improvement is a policy of Hobart, specifications are subject to change without notice.